



"Innovative Solutions for A Better Life"

UF S-210 : 7-Bores Capillary Ultrafiltration Module



DIMENSION	Nominal Diameter	2 inch
	Length	325 mm
	Feed/Concentrate Connection	1/4 "
	Permeate Connection	1/4 "
	Weight	788 gram
FEATURES	Permeate Capacity	50 liter/hour
	Permeate Turbidity	<3 NTU
	Filtration Mode	Lumen to Shell (Cross Flow)
	Membrane Material	Polysulfone
	7 Bores Fiber ID	0,9 mm
	Effective Surface Area	± 0,55 m ²
	Potting Material	Epoxy Resin
	Housing Material	PVC
	Storage Solution	0,1% Sodium Metabisulfite
OPERATION	Operating pressure	1,5 - 2,5 bar
	Operating temperature	max. 50 °C
CHEMICAL CLEANING	Acidic Cleaning	0,1% HCl solution
	Caustic Cleaning	0,1% NaOH solution

*For best cleaning result, please consult GDP Filter

The information contained in this publication is believed to be accurate and reliable, but is not to be construed as implying any warranty or guarantee of performance. We assume no responsibility, obligation or liability for results obtained or damages incurred through the application of the information contained herein.

GDP Filter - Filtration and Separation System

Jl. Cihanjuang No. 124 Km. 2,5 - Bandung 40559, Indonesia

Ph. : (022) 6648498, Fax. : (022) 6652139, E-mail : support@gdpfilter.co.id; Web : www.gdpfilter.co.id